



(c) NOTES:

1. METALSHELLS: COPPER ALLOY;
min. 315µin TIN over 40-80µin NICKEL
2. INSULATOR: TPE
3. CLAMPS: STAINLESS STEEL
4. SCREW: STAINLESS STEEL

(d) 5. CONNECTOR IS PART MARKED: PART NO. CONEC ABC

No. of pos.	A _{-0,76}	B _{+0,25}	C	D _{-0,3}	(d) E ₊₂₅	(d) F _{-0,76}	Part No.: Bulk package	Part No.: (e) Single package
9	31,19	16,79	25,00 ^{+0,12} _{-0,10}	6,12	8,23	12,93	165X14719X	165X14719XE
15	39,52	25,12	33,30 ^{+0,15}	6,12	8,23	12,93	165X14729X	165X14729XE
25	53,42	38,84	47,04 ^{+0,13}	5,99	8,23	12,93	165X14739X	165X14739XE
37	69,70	55,30	63,50 ^{+0,13} _{-0,11}	5,99	8,23	12,93	165X14749X	165X14749XE
50	67,31	52,68	61,10 ^{+0,14} _{-0,11}	5,99	10,95	15,75	165X14759X	165X14759XE

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH	DO NOT ALTER CAD DRAWING BY HAND			tolerance		 dim. in mm	scale: 2:1				
								material: SEE NOTES			
								title: HOOD 9 - 50pos. FOR SOCKET CONNECTOR water resiatant, shielded for EMI/RFI			
										dwg no: Inventor 10 DIN-A4 sh: 1	
								part no: 16K1A291A SEE TABLE			

