



SPECIFICATIONS

PARAMETERS	VALUES	UNITS
RATED VOLTAGE	1	Vp-p
OPERATING VOLTAGE RANGE	1 ~ 10	Vp-p
RATED CURRENT (MAX)	3	mA
CAPACITANCE	80,000 ± 30%	pF
MINIMUM SPL @ 1 CM	103	dB
RESONANT FREQUENCY	2,500 ± 500	Hz
OPERATING TEMPERATURE	-20 ~ +60	°C
STORAGE TEMPERATURE	-30 ~ +70	°C
HOUSING MATERIAL	ABS	-
TERMINAL MATERIAL	LEAD WIRE	-
WEIGHT	1.3	grams

THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, WITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.
©2003, Projects Unlimited Inc.


REVISION HISTORY

LTR	DESCRIPTION	DATE	APPROVED
-	RELEASED FROM ENGINEERING	10/26/2006	
A	REVISED RESONANT FREQUENCY	6/16/2008	B.R.
B	REVISED TO INVENTOR 3-D DRAWING TEMPLATE	6/16/2010	B.R.
C	REVISED RESONANT FREQUENCY	6/16/2010	B.R.
D	REVISED SPL DISTANCE	8/31/2010	B.R.



NOTES:

1. ALL DIMENSIONS ARE IN MILLIMETERS.
2. SPECIFICATIONS SUBJECT TO CHANGE OR WITHDRAWL WITHOUT NOTICE.
3. THIS PART IS RoHS 2002/95/EC COMPLIANT.

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS, TOLERANCES ARE ±0.5 AND ANGLES ARE ±3°.	SIZE A3	Designed by	Date	Checked by	Date	Approved by	Date	Drawn Date
		J.D.	10/26/2006	R.W.	10/26/2006	B.R.	10/26/2006	6/16/2010
AT-1803-T-LW50-R.idw		 pui audio a projects unlimited company				AT-1803-T-LW50-R Receiver		
						Edition		Sheet
						-		1 / 1