

150-31098

Article Number: 150-31098

Description: Fir Tree with Tie, 8.0" Long, Mounting Hole Diameter .26"-.28", PA46, Grey, 500/pkg



Base Data	Local Order Number	150-31098
	Type	T50RFT6LG
	Color	Gray (GY)
	Features and Benefits	<ul style="list-style-type: none"> • Staggered fir tree branch design provides low insertion forces and high extraction forces. • Initial fir tree serves as a locating feature for assistance in blind assembly applications. • Disc feature provides anti-rattle protection in high vibration applications.
	Quantity Per	bag
	Product Description	HellermannTyton's fir tree mounts provide a secure grip in a mounting hole and protect against dirt and other impurities. The mount can slide along the strap of the cable tie for proper orientation. The fir tree mounts are designed to provide a low insertion force and high extraction force. This mount is sold as an assembly with the cable tie.
	Short Description	Fir Tree with Tie, 8.0" Long, Mounting Hole Diameter .26"-.28", PA46, Grey, 500/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		222N
Length L (Imperial)		8.0"
Length L (Metric)		200mm
Length L2 (Imperial)		0.46"
Length L3 (imperial)		0.69"
Length L3 (metric)		17.5mm
Fixation Method		Fir Tree
Identification Plate Position		none
Length L2 (Metric)		11.6mm
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated

150-31098

HellermannTyton

Product Dimensions	Width W (Imperial)	0.18"
	Width W (Metric)	4.6mm
	Width W2 (Imperial)	0.35"
	Width W2 (Metric)	9.0mm
	Width W3 (Imperial)	0.2"
	Width W3 (Metric)	5.0mm
	Height H (Imperial)	0.05"
	Height H (Metric)	1.2mm
	Height H2 (Imperial)	0.44"
	Height H2 (Metric)	11.1mm
	Bundle Diameter Min. (Imperial)	0.06"
	Bundle Diameter Min. (Metric)	5.0mm
	Bundle Diameter Max. (Imperial)	2.0"
	Bundle Diameter Max. (Metric)	45.0mm
	Disc Diameter (Imperial)	0.63"
	Disc Diameter (Metric)	16.0mm
	Panel Thickness Max. (Imperial)	0.24"
	Panel Thickness Max. (Metric)	6.0mm
	Panel Thickness Min. (Imperial)	0.03"
	Panel Thickness Min. (Metric)	0.75mm
Mounting Hole Diameter D (Imperial)	0.26 - 0.28"	
Mounting Hole Diameter D (Metric)	6.4 - 7.1 mm	
Mounting Hole Diameter D Min. (Imperial)	0.26"	
Mounting Hole Diameter D Max. (Imperial)	0.28"	
Material and Specifications		
	Material	Polyamide 4.6 (PA46)
	Material Shortcut	PA46
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Metric)	500
	Customs Number(Schedule B)	3926909987
	Content Unit (BMEcat)	pieces

150-31098

HellermannTyton

Logistic and
Packaging

Weight (Metric)

1.5kg