



**Tripp Lite**  
 1111 West 35th Street  
 Chicago, IL 60609 USA  
 Telephone: +(773) 869 1234  
 E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: BP72V15-2U

### BP72V15-2U - External Battery Pack for UPS System

#### Highlights

- Extends runtime of select compatible Tripp Lite UPS Systems with 72VDC black 3-point external battery connector
- Simple installation; 2U rackmount, tower and stack adaptable



#### Description

BP72V15-2U rack/tower external battery pack offers extended battery runtime when used in conjunction with compatible Tripp Lite systems. Multi-use form factor supports configuration in stacking, upright tower and rackmount applications using only 2 rack spaces (2U). Upright tower configuration supported with optional 2-9USTAND accessory. Includes heavy gauge cabling with high current DC connector for simple installation. COMPATIBLE UPS SYSTEMS - SU3000RTXL2U, SU3000RTXL3U, SU3000RTXL3UHV, SU3000RTXR3U, SU3000RTXR3UHW, SUINT3000RTXL2U, SUINT3000RTXL3U, SU3000XL and other Tripp Lite UPS systems that specify the use of this battery pack.

#### Package Includes

- BP72V15-2U external battery pack
- Mounting hardware
- Warranty information
- Instruction manual

#### Features

- Offers extended-run UPS operation when used in conjunction with compatible Tripp Lite UPS systems
- Supports stacking or rackmount installation using only 2 rack spaces (2U)
- Supports upright tower installation with optional 2-9USTAND accessory
- Includes heavy gauge cabling with high current DC connectors for simple installation

#### Specifications

BATTERY	
Expandable battery runtime	No, a max quantity of ONE <a href="#">BP72V15-2U</a> can be connected to the host UPS system. If additional battery packs are to be connected, use an expandable model, like <a href="#">BP72V28RT-3U</a>
DC system voltage (VDC)	72
Connects to UPS via	DC connector
Typical battery lifespan	4-6 years typical (North America)
PHYSICAL	
Shipping weight (lbs)	120

<b>Shipping weight (kg)</b>	54.5
<b>Unit Dimensions (HWD/in)</b>	3.5 x 17.5 x 20.75
<b>Unit Dimensions (HWD/cm)</b>	8.9 x 52.7 x 52.7
<b>Shipping Dimensions (HWD/in)</b>	10 x 28.5 x 26.5
<b>Shipping Dimensions (HWD/cm)</b>	25.4 x 72.4 x 67.3
<b>Unit weight (lbs)</b>	72.4
<b>Unit weight (kg)</b>	32.9
<b>Material of construction</b>	Steel
<b>Form factors supported</b>	2U rack/tower
<b>WARRANTY</b>	
<b>Product Warranty Period (U.S. &amp; Canada)</b>	2-year limited warranty
<b>Product Warranty Period (International)</b>	1-year limited warranty
<b>Product Warranty Period (Mexico)</b>	1-year limited warranty
<b>Product Warranty Period (Puerto Rico)</b>	1-year limited warranty

## Related Items

### Optional Products

Related Model	Description	Qty.
<a href="#">WEXT3-BP72V</a>	3-Year Extended Warranty - For All 72V Battery Packs	1
<a href="#">WEXT5-BP72V</a>	5-Year Extended Warranty - For All 72V Battery Packs	1
<a href="#">2-9USTAND</a>	Enables Tower Placement of Rackmount UPS Systems	1
<a href="#">2POSTRMKITWM</a>	Enables 2-Post Rackmount or Wallmount Installation of Select Rackmount UPS Systems	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?variables.txtModelID=3019](http://www.tripplite.com/en/products/model.cfm?variables.txtModelID=3019).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.