

RoHS Compliance Statement

None of the following materials are intentionally added in manufacturing this product: lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE) as outlined in the Directive 2002/95/EC Article 4.1. See Desco Industries Inc. letter on-line at ProtektivePak.com.

DESCRIPTION

Use Protektive Pak Lead-Free Zone Aisle Marking Tape to mark your Lead-Free work area, or to designate areas within the manufacturing facility where Lead-Free component and assembly production takes place. All Protektive Pak rolls are manufactured in 54 foot long increments, and is itself RoHS compliant. None of the following materials are intentionally added in manufacturing: lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBB) or polybrominated diphenyl ethers (PBDE) as outlined in Directive 2002/95/EC Article 4.1.

COLOR: Green with White printing

SYMBOL: Pb-Free "LEAD-FREE ZONE"

PACKAGED: Roll, 3" diameter core

INK & VARNISH SPECIFICATIONS:

Alcohol Resistance: Excellent
Grease Resistance: Excellent
Rub Resistance: Excellent
Water Resistance: Excellent

OPERATING TEMPERATURE: -5° to 175°F

Minimum Labeling Temperature: +15°F

About RoHS directive:

The European DIRECTIVE 2002/95/EC Restriction on Hazardous Substances in Electrical and Electronic Equipment or "RoHS" mandates that new electrical electronic equipment must not contain lead, mercury, cadmium, hexavalent chromium, polybrominated biphenyls (PBBs) or polybrominated diphenyl ethers (PBDEs) starting on July 1, 2006.

PHYSICAL PROPERTIES: Thickness MIL (MICRON)	Value	Test Method
Film: Adhesive: OV Film:	3.25 +/-10% 0.75-0.85 +/-0.1 6	ASTM D 3652-83
Dimensional Stability		
MD:	<1.0	On Al panel at 160°F
TD:	<1.0	(70°C) for 24hr.

ADHESION PROPERTIES:	Average Expe		Expect	ed Range	
Adhesion from Stainless Steel: Acrylic: Glass:	oz/in 63 68 61	(N/m) (693) (748) (671)	oz/in 46-80 50-85 45-80	(N/m) (495-880) (550-935) (495-880)	PSTC 1 (Modified for 72 hr dwell time)
Expected Shear: (hours)	15				PSTC 7 (1hr dwell, 1 sq. in, 4lb. load)
Track (qm/sq. cm)	350		200-500	0	ASTM D 2979-88

EXPECTED EXTERIOR LIFE: Two years **SERVICE TEMPERATURE RANGE:** 40°f to 176° **MINIMUM APPLICATION TEMPERATURE:** 50°F (10°C)

STORAGE STABILITY: Two years stored at 70°F (21°C) and 50% H

Item	Description	Size	Qty/Roll
47103	Tape, Aisle Marking, Lead-Free Zone	3" x 54'	1

TAPE, AISLE MARKING, LEAD-FREE ZONE



PROTEKTIVE PAK 13520 MONTE VISTA AVENUE, CHINO, CA 91710 PHONE (909) 627-2578, FAX (909) 363-7331 ProtektivePak.com

DRAWING NUMBER 47103 **DATE**: 01/06