

January 2017

Wireless Power Transfer

Rx (recieving) coil modules

WRM483245-15F5-5V-G1

Wireless Power Transfer


Rx (recieving) coil modules


FEATURES

- This is Rx turnkey solution including receiving coil with attractor and modul for Wireless Power Transfer
- \bigcirc To achieve 5V x 1A output and operating fully WPC compliant
- O Pre cracked ferrite is available for durable construction
- Flexible sheet type is available

SHAPE & DIMENSIONS

(1.8MM MAX. THICKNESS MODULE)





W, L1, L2 dimensions	Efficiency	Thickness
(mm)	(%)Ref.	(mm)*
W1: 32		1.00mm max. (Coil)
L1: 48	72	
L2: 28		1.80mm max. (Module)

*Contact us for more information.

ELECTRICAL CHARACTERISTICS

CHARACTERISTICS SPECIFICATION TABLES

Rx coil unit		Rx modules				Part No.
Inductance	DC resistance	Output voltage	Output current	Efficiency	IC information	-
[100kHz, 1Vrms]	[25°C]					
(µH)	(Ω)max.	(V)	(A)	(%)Ref.		
13	0.27	4.95 to 5.05	0.3 to 1.0	72	TC7763WBG	WRM483245-15F5-5V-G1
10	0.27	4.00 10 0.00	0.0 10 1.0	12	(Toshiba IC)	

* Contact us for more information.

O RoHS Directive Compliant Product: See the following for more details.https://product.tdk.com/info/en/environment/rohs/index.html

O Halogen-free: Indicates that CI content is less than 900ppm, Br content is less than 900ppm, and that the total CI and Br content is less than 1500ppm.

A Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use. Please note that the contents may change without any prior notice due to reasons such as upgrading.

⊗TDK

Product compatible with RoHS directive Halogen-free

▲ Reminders

- Do not use or store in locations where there are conditions such as gas corrosion (salt, acid, alkali, etc.).
- Self heating (temperature increase) occurs when the power is turned ON, so the tolerance should be sufficient for the set thermal design.
- O Fully caution, if metal piece contacted with top of coil surface then it could be danger of generated heat.
- Do not use for a purpose outside of the contents regulated in the delivery specifications.
- O The products listed on this catalog are intended for use in general electronic equipment (AV equipment, telecommunications equipment, home appliances, amusement equipment, computer equipment, personal equipment, office equipment, measurement equipment, industrial robots) under a normal operation and use condition.

The products are not designed or warranted to meet the requirements of the applications listed below, whose performance and/or quality require a more stringent level of safety or reliability, or whose failure, malfunction or trouble could cause serious damage to society, person or property.

If you intend to use the products in the applications listed below or if you have special requirements exceeding the range or conditions set forth in the each catalog, please contact us.

- (1) Aerospace/aviation equipment
- (2) Transportation equipment (cars, electric trains, ships, etc.)
- (3) Medical equipment
- (4) Power-generation control equipment
- (5) Atomic energy-related equipment
- (6) Seabed equipment
- (7) Transportation control equipment

- (8) Public information-processing equipment
- (9) Military equipment
- (10) Electric heating apparatus, burning equipment
- (11) Disaster prevention/crime prevention equipment
- (12) Safety equipment
- (13) Other applications that are not considered general-purpose applications

CONTACT WINDOWS FOR MORE INFORMATION

Please note that the contents may change without any prior notice due to reasons such as upgrading.

Country	Person in charge	Web	
US	Chris Burket	chris.burket@us.tdk.com	
EU	Andre Carranque	Carranque@eu.tdk.com	
Japan	Takeshi Ishibashi	tishiba@jp.tdk.com	
TTW	ChienHung Lin	ChienHung_Lin@tw.tdk.com	
China	ChienHung Lin	ChienHung_Lin@tw.tdk.com	
Korea	Youngsoo m Kim	youngsoo_kim@kr.tdk.com	
ASEAN	ChienHung Lin	ChienHung_Lin@tw.tdk.com	

A Please be sure to request delivery specifications that provide further details on the features and specifications of the products for proper and safe use.