



T1M74-L-01-F

(2.54 mm) .100"

IPR1, T1M74-L, T1M74-R, MRTD, MRTDT SERIES

DISCRETE WIRE COMPONENTS & TOOLING

SPECIFICATIONS

For complete specifications see www.samtec.com?IPR1, www.samtec.com?T1M74-L or www.samtec.com?T1M74-R

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



TOOLING

- Hand Tool: CAT-HT-174-2030-13
- Mini Applicator (20-24 AWG): CAT-MA-174-2024-XX-01
- Mini Applicator (26-30 AWG): CAT-MA-174-2630-XX-01
- Extraction Tool: CAT-EX-74-01

TYPE	PINS PER ROW	D
I	-02, -03, -04, -05, -06, -08, -10, -12, -15 (Standard sizes)	-D = Double Row

Insulator Material: Nylon

TYPE	WIRE GAUGE	PLATING OPTION
T1M74-L = Contact, Loose	-01 = 26 to 30 AWG -02 = 20 to 24 AWG	-F = Gold flash on contact -L = 10 μ" (0.25 μm) Gold on contact

Contact Material: Phosphor Bronze

Mates with: MMSD(T)

SPECIFICATIONS

For complete specifications see www.samtec.com?MRTD or www.samtec.com?MRTDT

Insulator Material: Nylon 66

Contact Material: Phosphor Bronze

Plating: Au or Sn over 50 μ" (1.27 μm) Ni

Operating Temp Range: -40 °C to +105 °C (PVC) -55 °C to +125 °C (*Teflon®)

Wire: 20 to 30 AWG

RoHS Compliant: Yes

*DuPont™ Teflon® is a registered trademark of the E.I. du Pont de Nemours and Company or its affiliates.

RECOGNITIONS

For complete scope of recognitions see www.samtec.com/quality



Note: Teflon® cable is intended for crimp only. Contact Samtec for solderable cable applications.

TYPE	PINS PER ROW	WIRE GAUGE	PLATING OPTION	ASSEMBLY LENGTH	PINOUT
MRTD = Double Row PVC Cable	-02, -03, -04, -05, -06, -08, -10, -12, -15 (Standard sizes)	-20 -20C* -22 -24 -24C* -26 -28 -28C* -30	-L = 10 μ" (0.25 μm) Gold on contact	- "XX.X" = Assembly Length in Inches Single ended = (76.2 mm) 03.0" min. Double ended = (84.0 mm) 03.3" min.	Leave blank for single ended cable assembly. -L1 = Plastic Transfer Latch up, straight -L4 = Plastic Transfer Latch down, straight

APPLICATION

Note: Acceptable panel thickness of (0.84 mm) .0329" to (2.28 mm) .0897"