


Gecko with Latches Connectors

Female Cable Assemblies

- ❏ 4-finger Beryllium Copper contact.
- ❏ No. 1 position identified on moulding.
- ❏ 2A current capacity, resists high vibration and shock.
- ❏ Withstands extremes of temperature: -65°C to +150°C.
- ❏ Back potted for added strain relief.
- ❏ For non-standard cable lengths, please contact technical@harwin.com with your requirements.



PART NUMBERING SYSTEM

G125 - F C X XX 05 L0 - XXXX X

SERIES CODE

GENDER - FIRST END

F	Female
----------	--------

CABLE SIZE

1	26 AWG
2	28 AWG
3	30 AWG
4	32 AWG

TOTAL NO. OF CONTACTS

06, 10, 12, 16, 20, 26, 34, 50

TERMINATION - SECOND END

L	Loose cut end
F	Female connector

CABLE LENGTH

0150	150mm
0300	300mm (double-ended)
0450	450mm (single-ended)

LATCHES

L0	No Latches
-----------	------------


FINISH

05	Gold
-----------	------

Female Cable Assemblies

- ❖ See previous page for cable length options.
- ❖ Cable assemblies are constructed with Contact 1 attached to Contact 1, Contact 2 to Contact 2, etc.


FEMALE SINGLE ENDED



ORDER CODE

G125-FCXXX05L0-XXXXL

FEMALE - FEMALE



ORDER CODE

G125-FCXXX05L0-XXXXF

All dimensions in mm.

Patent Published