

111-24801



Article Number: 111-24801

Description: Heavy-Duty Cable Tie, 20.3" Long, 250lb Tensile Strength, PA66, Black, 25/pkg

Base Data	
Local Order Number	T250R0X2
Type	T250R
Color	Black (BK)
Features and Benefits	<ul style="list-style-type: none"> • Heavy duty design to offer higher tensile strength. • Buckle feature on head allows excess strap to be tucked away after installation.
Quantity Per	bag
Product Description	HellermannTyton heavy duty cable ties offer a higher tensile strength for heavy load applications. The head design guarantees high tensile strength, as well as a low insertion force. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
Short Description	Heavy-Duty Cable Tie, 20.3" Long, 250lb Tensile Strength, PA66, Black, 25/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	250.0lbs
Minimum Tensile Strength (Metric)	1115.0N
Length L (Imperial)	20.3"
Length L (Metric)	515.0mm
Fixation Method	None
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.49"
Width W (Metric)	12.5mm
Bundle Diameter Min. (Imperial)	0.47"
Bundle Diameter Min. (Metric)	12.0mm
Bundle Diameter Max. (Imperial)	4.9"
Bundle Diameter Max. (Metric)	125.0mm

111-24801



Product Dimensions	Thickness T (Metric)	1.9mm
Material and Specifications	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	Certification/Specification	UL-ZODZ2.E64139
	UL Recognized (US and Canada)	Yes
	Logistic and Packaging	Package Quantity (Imperial)
Package Quantity (Metric)		25
Customs Number(Schedule B)		3926909987