




PLUG, 3 SOCKET, AT SERIES, END CAP

AT06-3S-EC01XXX

A3







NOTES: UNLESS OTHERWISE SPECIFIED

MATERIAL:

HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

2. MODIFICATIONS: END CAP

3. SPECIFICATIONS:

3.1 CURRENT RATING: 13 AMPS

3.2 OPERATING TEMPERATURE: -55°C TO +125°C

3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.

3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.

3.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION)

3.6 MATING CYCLE DURABILITY: 100 CYCLES

3.7 RoHS COMPLIANT

4. MATING PART: AT04-3P* RECEPTACLE (* = MODIFICATIONS AND COLORS)

5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

6 CONTACT SIZE AND REAR SEAL WIRE RANGE:

CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL
SIZE	O.D.	O.D.	WIRE RANGE
16	2.24 mm (.088 in)	3.68 mm (.145 in)	14 - 20 AWG

