
THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, MITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.


© 2005, Projects Unlimited Inc.

SPECIFICATIONS

PARAMETERS	VALUES	UNITS
DIRECTIVITY	OMNI	_
SENSITIVITY	-40±3	dB
STANDARD OPERATING VOLTAGE	2	Vdc
MAX OPERATING VOLTAGE	10	Vdc
CURRENT CONSUMPTION MAX	0.5	mA
IMPEDANCE	2.2	kOhm
SIGNAL TO NOISE RATIO (MIN.)	60	dB
TERMINAL	PINS	-
INTERNAL CAPACITOR	33	pF

		REVISIONS		
LTR DESCRIPTION		DESCRIPTION	DATE	APPROVED
	-	RELEASED FROM ENGINEERING	3/23/06	





NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2002/95/EC COMPLIANT.
- 4. MICROPHONE CLOTH OVER FACE IS IP51 RATED.

FILE NAME	
POM-2240P-C33-R.DW0)

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MILLIMETERS, TOLERANCES ARE ±0.5 AND ANGLES ARE ±3.		projects ® unlimited Dayton , Ohio		
APPROVALS DATE		MICROPHONE		
DRAWN TG	5/05			
CHECKED B.R.	5/05	SIZE DRAWING NO. A POM-2240P-C33-F		
APPROVED R. W.	5/05	A FUM-2240F-033-F	`	
DO NOT SCALE DRA	WING	SCALE: N.T.S. SHEET 1 OF	l	