

Article Number: 170-03005

Description: Braided Sleeving, Expandable, 1.5" Dia, PET, Black, 40

ft/reel

| Base Data | | |
|--------------------------------|---------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | | |
| | Local Order Number | 170-03005 |
| | Туре | BSP1120 |
| | Color | Black (BK) |
| | Features and Benefits | Weave construction adjusts to twisting and flexing without creating wrinkles or bends. Durable construction offers excellent abrasion and cut-through resistance as well as inertness to most chemicals and fungus. Color options available to provide easy visual and safety identification of critical wiring components. Expands to 150% of nominal diameter for fast, easy installation. |
| | Quantity Per | reel |
| | Product Description | General purpose expandable braided sleeving provides flexible abrasion protection for wire bundles and hoses. |
| | Short Description | Braided Sleeving, Expandable, 1.5" Dia, PET, Black, 40 ft/reel |
| Product Dimensions | | |
| | Length L (Imperial) | 40.0ft |
| | Length L (Metric) | 12.2m |
| | Reel Length (imperial) | 40.0ft |
| | Bundle Diameter Min. (Imperial) | 1.0" |
| | Bundle Diameter Min. (Metric) | 25.4mm |
| | Bundle Diameter Max. (Imperial) | 2.125" |
| | Bundle Diameter Max. (Metric) | 54.0mm |
| | Nominal Diameter (Imperial) | 1-1/2" |
| | Nominal Diameter (Metric) | 38.1mm |
| Material and Specifications | | |
| | Material | Polyester (PET) |
| | Material Shortcut | PET |

generated on: 4/28/2017

170-03005



| Material and Specifications | Flammability | UL 94 V0 |
|--------------------------------|-------------------------------|-----------------------------------|
| | Halogenfree | Yes |
| | Operating Temperature | -94°F to +248°F (-70°C to +125°C) |
| | ROHS Compliant | Yes |
| | UL Recognized (US and Canada) | Yes |
| Logistic and Packaging | | |
| | Package Quantity (Imperial) | 40ft |
| | Package Quantity (Metric) | 12.19m |
| | Customs Number(Schedule B) | 3926909987 |
| | Weight (imperial) | 0.79lbs |
| | Weight (Metric) | .358kg |

generated on: 4/28/2017