## **HellermannTyton**



Article Number: 170-03053

Braided Sleeving, Resin Coated Fiberglass, 1" Dia, GF, Black, 100 ft/bulk reel

Base Data		
	Local Order Number	170-03053
	Туре	BSHTFG100B
	Color	Black (BK)
	Features and Benefits	An extremely tough sleeving material which provides thermal protection up to
		<ul> <li>An external protection up to 1,200°F.</li> <li>Sturdy construction maintains its tight structure under extreme shaking, scraping, pressure and varying temperature conditions.</li> <li>Cuts easily with ordinary scissors for easy application.</li> <li>UL VW-1 flammability rating for use in conditions requiring a very high degree of flame resistance.</li> </ul>
	Quantity Per	reel
	Product Description	An extremely high-temperature resistant sleeving designed to protect wires and cables subjected to continuous temperature variations, vibration, abrasion, and mechanical stress.
	Short Description	Braided Sleeving, Resin Coated Fiberglass, 1" Dia, GF, Black, 100 ft/bulk reel
Product Dimensions		
	Length L (Imperial)	100.0ft
	Length L (Metric)	30.48m
	Reel Length (imperial)	100.0ft
	Bundle Diameter Max. (Imperial)	1.625"
	Bundle Diameter Max. (Metric)	41.3mm
	Diameter D (imperial)	1.0"
	Nominal Diameter (Imperial)	1"
	Nominal Diameter (Metric)	25.4mm
Material and Specifications		
	Material	Glass Fiber (GF)
	Material Shortcut	GF
	Flammability	VW-1

## 170-03053

## **HellermannTyton**

Material and Specifications	Operating Temperature	-94°F to +1202°F (-70°C to +650°C)
	ROHS Compliant	Yes
	UL Recognized (US)	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100ft
	Package Quantity (Metric)	30.48m
	Customs Number(Schedule B)	7019901000
	Weight (imperial)	10.5lbs
	Weight (Metric)	4.76kg