## **HellermannTyton**



Article Number: 169-60020

Description: Convoluted Tubing, Slit, .75" Dia, PA6, Black with Gray Stripe, 100 ft/pkg

Base Data		
	Local Order Number	169-60020
	Туре	CTN340
	Color	Black with Gray Stripe (BKSTGY)
	Features and Benefits	<ul> <li>Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture</li> <li>Tubing protects cables and wires against automotive fluids, vibration wear</li> <li>Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight</li> </ul>
	Quantity Per	box
	Product Description	HellermannTyton's Convoluted Tubing, also known at Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.
	Technical Description	Convoluted Tubing, Slit, 3/4" Dia., PA6, Black w/Gray Stripe
	Short Description	Convoluted Tubing, Slit, .75" Dia, PA6, Black with Gray Stripe, 100 ft/pkg
Product Dimensions		
	Length L (Imperial)	100.0ft
	Length L (Metric)	30.5m
	Inner Diameter D (Imperial)	0.759"
	Inner Diameter D (metric)	19.28mm
	Diameter D (imperial)	0.989"
	Diameter D (metric)	25.12mm
	Diameter D2 (imperial)	0.759"
	Diameter D2 (metric)	19.28mm
	Outside Diameter D (imperial)	0.989"
	Outside Diameter D (metric)	25.12mm
	Nominal Diameter (Imperial)	3/4"

## 169-60020

## HellermannTyton

Product Dimensions	Nominal Diameter (Metric)	19.05mm
	Wall Thickness WT (Imperial)	.005"
	Wall Thickness WT (Metric)	0.127mm
Material and Specifications		
	Material	Polyamide 6 (PA6)
	Material Shortcut	PA6
	Flammability	UL 94 HB
	Operating Temperature	-40°F to +300°F (-40°C to +149°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	100ft
	Package Quantity (Metric)	30.48m
	Customs Number(Schedule B)	3926909987