Linear Position Sensors (for reference only)

Japan Malaysia

EVAWA, EVAWM (Slim Type) EVAW7 (Headlight Sensor)




■ Features

- High performance that guarantees a terminal-based linearity within ±0.5%
- A wide variety of operation strokes
- Long life and high resolution

■ Recommended Applications

- Detection of still camera/camcorder lens positions
- Detection of car seat positions
- Steering wheel tilt and telescopic controller
- Car headlight angle detection sensor

■ Explanation Part Numbers



Specifications

		EVAJ, EVAWA, EVAWM	EVAW7	
Mechanical	Stroke	13.0 mm±0.5 mm 18.0 mm±0.5 mm 32.0 mm±0.5 mm	9.0 mm±0.5 mm	8.0 mm±0.5 mm
	Operating Force	0.25 N max. (Measurement speed: 5 mm/s to 25 mm/s)	2 N max.	1 N max.
Electrical	Linearity	±1 % (±0.5 %)	±2 %	±1 %
	Total Resistance	10 kΩ±30 %	10 kΩ±30 %	4.7 kΩ±30 %
	Voltage Rating	5 Vdc max.	5 Vdc max.	12 Vdc max.
	Taper	В	В	
Endurance	Operating Life	100000 cycles min. (Type capable of 200000 or more operaton is also available)	10000 cycles min.	10000 cycles min.
Minimum Quantity/Packing Unit		100 pcs. (Tray Pack)	300 pcs. (Tray Pack)	200 pcs. (Tray Pack)
Quantity/Carton		500 pcs.	3000 pcs.	2000 pcs.

■ Dimensions in mm (not to scale)

