

FIBERGLASS OMNIDIRECTIONAL ANTENNAS FG9023



Americas: +1.847 839.6907

IAS-AmericasEastSales@lairdtech.com

Europe: +44.1628.858941 IAS-EUSales@lairdtech.com

Asia: +86.21.5855.0827.127

IAS-AsiaSales@lairdtech.com

www.lairdtech.com

FIBERGLASS BASE STATION ANTENNAS FEATURE INDUSTRY-LEADING DESIGN COMPONENTS THAT PERFORM IN EXTREME CONDITIONS

Laird Technolgies' fiberglass base station antennas are collinear designs enclosed in a high density fiberglass, which is covered with a protective ultraviolet inhibiting coating.

The radiating elements are made from high efficiency copper and are carefully phased to provide maximum gain in the horizontal plane. The mounting sleeves are tuned to eliminate RF currents from the transmission line, resulting in a "cold" sleeve allowing great freedom in mounting. This high quality and well-focused beam provides the highest gain and best efficiency.

FEATURES AND BENEFITS:

• Every FG fiberglass base antenna is tested on a network analyzer before shipping to assure the best performance.

902 - 928 MHz

< 2:1 Max

3 dBd

200 W

Ω50

Vertical

70° x 360°

None

Omnidirectional

N Female connector

125 mph (210 kph)

85 mph (137 kph)

57 lbs (26 kg)

0.2104 sq. ft.

FM2 Mounting Kit

(Sold separately)

LABH350NN (Sold separately)

Lightning Arrestor

23-3/8"

1.310"

< 1 lbs

- Special UV Treated stands up to the sun
- Durable gold anodized sleeve and cap
- with N Female connector
- Custom tuning available

Frequency Range

Maximum Power

Nominal Impedance

Half-Power Beamwidth

(Elevation[°] x Azimuth[°])

Lightning Protection

Rated Wind Velocity

Rated Wind Velocity

(with 0.5" radial ice)

125mph wind velocity Wind Resistance

Mounting Information

Lateral Thrust @

Nominal Gain

Polarization

Coaxial Cable

Length & Type

Termination

Height


Diameter Weight

Pattern


VSWR

APPLICATIONS:

- Omnidirectional (circular) outdoor antenna applications used by private organizations and government agencies around the globe.
- Typical applications include land based and marine radio and data transmissions for public safety agencies, commercial organizations, and the military.



Elevation Pattern (Y, Z, or H-plane)



Azimuthal Pattern (Y, Z, or E-plane)

ANT-DS-FG9023 0610

Any information furnished by Laird Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird materials rests with the end user, since Laird and its agents cannot be aware of all potential uses. Laird makes no warranties as to the fitness, merchantability or suitability of ny Laird makes no warranties as to the fitness, merchantability or suitability of ny Laird marker for any specific or general uses. Laird shall not be liable for incidental or consequential damages of any kind. All Laird products are sold pursuant to the Laird Terms and Conditions of sale in effect from time to time, a copy of which will be truished upon request. © Copyright 2015 Laird Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Logo, and other marks are trade marks or registered trade marks of Laird Inc. na Alfiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird or any third party intellectual property rights.