

181-00139



Article Number: 181-00139

Description: Panel Rivet, PA66, Natural, 1000/bag

Base Data	Local Order Number	PR1M4
	Type	PR1
	Color	Natural (NA)
	Features and benefits	<ul style="list-style-type: none"> • Panel rivets are made with nylon material to hold duct securely to the panel without corroding, ensuring longevity. • Panel rivets can be easily inserted with use of a specially designed, long shafted panel rivet tool. • Ergonomic design of the tool ensures effortless use when inserting rivets into deep channels or locations difficult to access.
	Quantity Per	EA
	Product Description	HellermannTyton panel rivets are one piece drive rivets that provide a fast, economic means of affixing wiring duct. The rivet is inserted into a 3/16" pre-punched hole and the pin is driven into the base, thereby expanding the rivet legs and locking the duct and sub-panel in place. The panel thickness (including the duct thickness) should be a maximum of 3/16".
	Technical Description	Panel Rivet
	Short Description	Panel Rivet, PA66, Natural, 1000/bag
	Product Dimensions	
	Minimum Tensile Strength (Imperial)	107.0lbs
	Minimum Tensile Strength (Metric)	478N
	Panel Thickness Max. (Imperial)	0.28"
	Panel Thickness Max. (Metric)	7.0mm
	Panel Thickness Min. (Imperial)	0.15"
	Panel Thickness Min. (Metric)	3.9mm
	Mounting Hole Diameter D (Imperial)	0.2"
	Mounting Hole Diameter D (Metric)	5.0 mm
	Diameter Max. (Imperial)	0.02"
	Diameter Max. (Metric)	0.51mm

181-00139

Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +176°F (-40°C to +80°C)
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3925900000