

92652-003LF 6 92652-004LF 8 92652-005LF 10 92652-006LF 12	DIM K DIM L U N A S S I G N E 200/5.08 .100/2.54 300/7.62 .200/5.08 400/10.16 .300/7.62 500/12.70 .400/10.16 600/15.24 .500/12.70	RETENTION ROD P/N D 65048-040 65048-040 65048-040 65048-040	RETENTION ROD LENGTH DIM A 1.300/33.02 1.300/33.02 1.300/33.02	PRODUCT NO 92652-026LF 92652-027LF 92652-028LF 92652-029LF	NO. OF POSITIONS 52 54 56	DIM K 2.600/66.04 2.700/68.58 2.800/71.12	DIM L 2.500/63.50 2.600/66.04	RETENTION ROD P/N 65048-013 65048-013	RETENTION ROD LENGTH DIM A 3.450/87.60 3.450/87.60
92652-002LF 4 .2 92652-003LF 6 .2 92652-004LF 8 .4 92652-005LF 10 .5 92652-006LF 12 .6	200/5.08 .100/2.54 300/7.62 .200/5.08 400/10.16 .300/7.62 500/12.70 .400/10.16	65048-040 65048-040 65048-040	1.300/33.02 1.300/33.02 1.300/33.02	92652-027LF 92652-028LF	54	2.700/68.58	, 2.600/66.04		3.450/87.6
92652-003LF 6 92652-004LF 8 92652-005LF 10 92652-006LF 12	300/7.62 .200/5.08 400/10.16 .300/7.62 500/12.70 .400/10.16	65048-040 65048-040	1.300/33.02 1.300/33.02	92652-028LF			,	65048-013	3.450/87.6
92652-004LF 8 .4 92652-005LF 10 .5 92652-006LF 12 .6	400/10.16 .300/7.62 500/12.70 .400/10.16	65048-040	1.300/33.02		56	2.800/71.12	0 700 /00 50		
92652-005LF 10 .5 92652-006LF 12 .6	500/12.70 .400/10.16			92652-029LF			2.700/68.58	65048-013	3.450/87.6
92652-006LF 12 .6	, ,	65048-040			58	2.900/73.66	2.800/71.12	65048-013	3.450/87.6
	600 /15 24 500 /12 70		1.300/33.02	92652-030LF	60	3.000/76.20	2.900/73.66	65048-005	4.650/118.1
92652-007LE 14	600/15.24 .500/12.70	65048-040	1.300/33.02	92652-031LF	62	3.100/78.74	3.000/76.20	65048-005	4.650/118.1
	700/17.78 .600/15.24	65048-040	1.300/33.02	92652-032LF	64	3.200/81.28	3.100/78.74	65048-005	4.650/118.1
92652-008LF 16 .8	800/20.32 .700/17.78	65048-040	1.300/33.02	92652-033LF	66	3.300/83.82	3.200/81.28	65048-005	4.650/118.1
92652-009LF 18 .9	900/22.86 .800/20.32	65048-040	1.300/33.02	92652-034LF	68	3.400/86.36	3.300/83.82	65048-005	4.650/118.1
92652-010LF 20 1	.000/25.40 .900/22.86	65048-026	2.300/58.42	92652-035LF	70	3.500/88.90	3.400/86.36	65048-005	4.650/118.1
92652-011LF 22 1	.100/27.94 1.000/25.40	65048-026	2.300/58.42	92652-036LF	72	3.600/91.44	3.500/88.90	65048-005	4.650/118.1
92652-012LF 24 1	.200/30.48 1.100/27.94	65048-026	2.300/58.42						
92652-013LF 26 1	.300/33.02 1.200/30.48	65048-026	2.300/58.42						
92652-014LF 28 1	.400/35.58 1.300/33.02	65048-026	2.300/58.42						
92652-015LF 30 1	.500/38.10 1.400/35.56	65048-026	2.300/58.42						
	.600/40.64 1.500/38.10	65048-026	2.300/58.42						
92652-017LF 34 1	.700/43.18 1.600/40.64	65048-026	2.300/58.42						
	.800/45.72 1.700/43.18	65048-026	2.300/58.42						
92652-019LF 38 1	.900/48.26 1.800/45.72	65048-026	2.300/58.42						
92652-020LF 40 2	2.000/50.80 1.900/48.26	65048-013	3.450/87.63						
92652-021LF 42 2	2.100/53.34 2.000/50.80	65048-013	3.450/87.63						
92652-022LF 44 2	2.200/55.88 2.100/53.34	65048-013	3.450/87.63						
92652-023LF 46 2	2.300/58.42 2.200/55.88	65048-013	3.450/87.63						
92652-024LF 48 2	2.400/60.96 2.300/58.42	65048-013	3.450/87.63						
92652-025LF 50 2	2.500/63.50 2.400/60.96	65048-013	3.450/87.63						

PDM: Rev:G STATUS: Released Printed: Sep 15, 2009