

Data Sheet



## No hassle warranty

NO HASSL

No waiting.

No shipping charges.

Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)

# WT-40 Dual display pH, mV & TEMP Meter

Keep the costs and risks of maintaining water quality, distribution and waste under control with these easy to use, one touch water management tester. Allows facility managers to take control of monitoring regulatory compliance and troubleshoot corrosion in building water/waste water systems.

- Used to check pH in water testing and treatment applications
- Dual LCD display with pH / mV and temperature (selectable C and F)
- USB port for data download to a PC (cable & software optional)
- Backlight display for use in dark areas
- pH electrode with Automatic Temperature Compensation for measurement accuracy
- 3 points pH calibration with automatic buffer recognition to prevent calibration errors
- Data Hold
- Max/Min and Data Recording
- Low bat indicator
- Auto power off
- Applications include : Pools, Spas, Aquariums, Labs, Aquaculture, Sanitation plants, Car washes, hydroponics, Water & Wastewater treatment and Boilers / Steam generator maintenance





## WT-40 Dual display pH, mV & TEMP Meter

## Data Sheet

### **Specifications**

pH Range	0.00~14.00
with High Resolution	0.01pH
pH Accuracy	±0.02pH
mV Range	-199.9 ~ +199.9mV, -1999 ~ +1999mV
mV Resolution	0.1mV( -199.9~+199.9 ) or 1mV (-1999~+1999 )s
mV Accuracy	±0.2mV( -199.9~+199.9 ) or ±2 mV (-1999~+1999 )
Temperature compensation	-5°C to 80°C (23°F to 176°F)
Accuracy	±0.3°C (± 31.5°F to 32.5°F)
Operating Temperature	0°C to 50°C (32°F to 122°F), Max.80%RH
Power Requirements	4x1.5V batteries AAA
Dimension	175 x 70 x 33 mm (6.9 x 2.8 x 1.3 in)
Weight	Approx. 157g (0.35 lb)
Package Contains	Meter, Battery, Instruction manual, Carrying Pouch, Probe, pH Standard Solution

#### Amprobe® Test Tools

website: www.Amprobe.com email: info@amprobe.com Everett, WA 98203 Tel: 877-AMPROBE

#### **Amprobe® Test Tools Europe**

In den Engematten 14 79286 Glottertal, Germany Tel.: +49 (0) 7684 8009 - 0

©2009 Amprobe Test Tools. All rights reserved. 7/2009 3520508 Rev A